

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 1/9

1 - IDENTIFICATION

GHS Product identifier: Jimo Limpa Tecidos Aerossol

Other means of identification: 49888

Recommended use of the chemical: Clean fabrics.

Specific restrictions on use: There are not known restrictions on use.

Supplier's details: Jimo Química Industrial Ltda.

Address: Rua Ítalo Raffo 693 - Distrito Industrial, CEP: 94930-240 - RS - Brasil.

Phone number: +55 51 3470 67 55

Email: jimo@jimo.com.br

Emergency phone number: +55 51 3470 67 55 / 0800 051 41 46

2 - HAZARD IDENTIFICATION

Classification of the substance or mixture: Aerosols - Category 2;
Skin Corrosion/Irritation - Category 3;
Serious eye damage/eye irritation - Category 2A;
Reproductive Toxicity - Category 1A;
Specific Target Organ Toxicity – Single Exposure - Category 3 - Narcotic;
Specific Target Organ Toxicity – Repeated Exposure - Category 1;
Hazardous to the Aquatic Environment - Acute Hazard - Category 3;
Hazardous to the Aquatic Environment - Chronic Hazard - Category 3.

Classification system adopted: Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

GHS label elements, including precautionary statements

Pictograms:



Signal word: DANGER

Hazard statement(s): H223 Flammable aerosol.
H229 Pressurized container: may burst if heated.
H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.
H372 Causes damage to the liver through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s):

PREVENTION:

P203 Obtain, read and follow all safety instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 2/9

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash hands thoroughly after handling.
 P264 + P265 Wash hands thoroughly after handling. Do not touch eyes.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

RESPONSE TO EMERGENCY:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P318 IF exposed or concerned, get medical advice.
 P319 Get medical help if you feel unwell.
 P332 + P317 If skin irritation occurs: Get medical help.
 P337 + P317 If eye irritation persists: Get medical help.

STORAGE:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSITION:

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in classification: The material has no other hazards.

3 - COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURE

Components contributing to the hazard: Ethylic alcohol (CAS 64-17-5): 20 - 30 %;
 Liquefied Petroleum Gas (LPG) (CAS 68476-85-7): 1 - 10 %;
 Diethylene glycol butyl ether (CAS 112-34-5): 1 - 10 %;
 Propylene glycol ether (CAS 1569-01-3): 1 - 10 %;
 Lauryl alcohol 7 EO (CAS 68439-50-9): 0.1 - 1 %;
 Myristic Oxide Amine (CAS Not applicable): 0.1 - 1 %;
 Diquaternary polydimethylsiloxane (CAS Not applicable): 0.1 - 1 %;
 N-Ethyl-N-Soy Morpholine Ethosulfate (CAS 61791-34-2): 0.1 - 1 %;
 Fragrance 1 CT Power EU Block (CAS Not applicable): 0.1 - 1 %;
 Sodium nitrite (CAS 7632-00-0): 0.1 - 1 %.

4 - FIRST-AID MEASURES

Description of necessary first-aid measures

Inhalation: Gases and vapors can cause dizziness or suffocation. Remove victim to fresh air and keep in a position that does not obstruct breathing. Monitor respiratory function. If the victim is breathing hard, give oxygen. If necessary, apply artificial respiration. Consult a doctor. Bring this document.

Skin: In case of contact of the material in pressurized form with the skin, injury or frostbite may occur. Wash exposed skin with a sufficient amount of water. Clothing that adheres to the skin should be

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 3/9

Eye:	thawed with warm water before being removed. Consult a doctor. Bring this document.
Ingestion:	Wash the victim's mouth with plenty of water. Never give anything by mouth to an unconscious person. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.
Most important symptoms/effects, acute and delayed:	Causes mild skin irritation with redness and dryness. Causes serious eye irritation with redness and pain. May cause drowsiness or dizziness, may cause dizziness and nausea. Causes damage to the liver through prolonged or repeated exposure.
Indication of immediate medical attention and special treatment needed, if necessary:	Avoid contact with the material when helping the victim. If necessary, symptomatic treatment should include, above all, supportive measures such as correction of hydro electrolytic and metabolic disorders and respiratory assistance. In case of skin contact, do not rub the affected area.

5 - FIRE-FIGHTING MEASURES

Extinguishing media:	Appropriate: carbon dioxide (CO ₂), water mist and dry chemical powder. Inappropriate: water directly onto the burning material.
Specific hazards arising from the chemical:	Combustion of the material or its packaging can form irritating and toxic gases such as carbon monoxide and dioxide. Very dangerous when exposed to excessive heat or other sources of ignition such as: sparks, open flames or flames from matches and cigarettes, welding operations, pilot lights and electric motors. Gases can be denser than air and can accumulate in low-lying or confined areas such as storm drains and basements. It can travel great distances causing the flame to retreat or new fires in both open and confined environments. Containers may explode if heated.
Special protective actions for fire-fighters:	Do not extinguish fire on gas leaks unless the leak can be contained. If the load is involved in fire, isolate and evacuate the area to a minimum radius of 1600 meters. Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing. Containers and tanks involved in the fire must be cooled with water mist.

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel:	Isolate the leakage from sources of ignition. Keep unauthorized persons out of the area and away from windows. Stop the leakage if it can be done without risk. Prevent sparks or flames. Do not smoke. Do not touch damaged containers or spilled material without proper clothing. Avoid exposure to the material. Stay in a safe place, with the wind at your back. Use personal protective equipment as described in section 8.
For emergency responders:	Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.
Environmental precautions:	Avoid that the spilled material reaches waterways or sewage system.
Methods and materials for containment and cleaning up:	For the gas phase: Release contents slowly into the atmosphere. Stay downwind. Do not pour water into the spill or the source of the leakage. Due to the dispersion of the material in the environment, it is recommended that the area be ventilated until the release the place. All equipment used to contain the material must be grounded. Do not dispose of used or damaged containers directly into the environment or sewage system. For the liquid phase: Use water mist to reduce material dispersion. Use natural or spill containment barriers. Collect spilled materials and place them in appropriate containers. Adsorb the remaining material with dry sand, earth, vermiculite, or any inert product. Place the adsorbed material in proper

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 4/9

containers and remove them to a safe place. Use non-sparking tools to pick up absorbed material. For final disposal, proceed according to Section 13 of this document.

7 - HANDLING AND STORAGE

Precautions for safe handling

Precautions for safe handling:	Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid gases and aerosols formation. Avoid exposure to the material, since the effects may not be felt immediately. Use personal protective equipment as described in section 8. Avoid contact with incompatible materials.
General hygiene:	Wash hands and face thoroughly after handling and before eating, drinking, smoking, or using the toilet. Contaminated clothing should be changed and washed before reuse. Remove contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including any incompatibilities

Technical measures for prevention of fire and explosion:	Keep away from heat, sparks, open flame, and hot surfaces. Do not smoke. Keep the container tightly closed. Ground the container vessel and material receiver during transfers. Only use non-sparking tools. Avoid the accumulation of electrostatic charges. Use explosion-proof electrical, ventilation, and lighting equipment.
Conditions for safe storage, including any incompatibilities:	Store in a dry, well-ventilated place away from sunlight. Keep the container closed. It is not necessary addition of stabilizers and antioxidants to ensure the durability. This material may react dangerously with some incompatible materials as outlined in Section 10. Keep away from incompatible materials.
Packaging compatibilities:	Similar to the original packaging.
Inadequate packaging materials:	There are not known unsuitable material.

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limit:	<p>The values below apply to workplaces.</p> <p>- <u>Ethylic alcohol</u>: OSHA - PEL - TWA: 1000 ppm (1900 mg/m³) (29 CFR 1910.1000 Table Z-1) (CFR); NIOSH - REL - TWA: 1000 ppm (1900 mg/m³); ACGIH - TLV - STEL: 1000 ppm;</p> <p>- <u>Liquefied Petroleum Gas (LPG)</u>: OSHA - PEL - TWA: 1000 ppm; 1800 mg/m³; NIOSH - REL - TWA: 1000 ppm (1800 mg/m³); ACGIH - TLV - TWA: See Appendix F: Minimal Oxygen Content (D; EX);</p> <p>- <u>Diethylene glycol butyl ether</u>: ACGIH - TLV - TWA: 10 ppm (IFV);</p> <p>- <u>Triethanolamine</u>: ACGIH - TLV - TWA: 5 mg/m³.</p> <p>CFR: See mentioned item in OSHA CFR; D: Simple asphyxiant; EX: Explosion hazard: the substance is a flammable asphyxiant or excursions above the TLV® could approach 10% of the lower explosive limit; IFV: Inhalable fraction and vapor.</p>
Biological limit:	Not established.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 5/9

Other limits and values: Not established.

Appropriate engineering controls: A risk assessment is recommended to define the engineering control measures necessary to eliminate or minimize the risk. These measures help to reduce exposure to the material. Maintain atmospheric concentrations of the constituents of the material below occupational exposure limits indicated.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection: Safety glasses.

Skin protection: Closed shoes and suitable protective clothing. Appropriate protective gloves.

Respiratory protection: A risk assessment should be performed for proper definition of respiratory protection, in view of the material use conditions.

Thermal hazards: It does not present thermal hazards.

9 - PHYSICAL AND CHEMICAL PROPERTIES

Aspect: Liquid, compressed.

Color: Colorless.

Odour: Characteristic.

Melting point/freezing point: Not applicable.

Boiling point or initial boiling point and boiling range: 83.5 to 103.5 °C (182.3 to 218.3 °F).

Flammability: Not available.

Lower and upper explosion limit/flammability limit:

Flash point: 36.3 °C (97.34 °F) - Closed cup.

Auto-ignition temperature:

Decomposition temperature:

pH: 8 to 9.5.

Kinematic viscosity:

Solubility(ies): Miscible in water.

Partition coefficient n-octanol/water (log value): Not available.

Vapour pressure: Not applicable.

Relative vapour density: Not applicable.

Density and/or relative density: Absolute density: 0.9 to 1 g/cm³ at 25 °C (77 °F).

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 6/9

Particle characteristics: Not applicable.

Other information: Not applicable.

10 - STABILITY AND REACTIVITY

Reactivity: Reactivity is not to be expected under normal conditions of temperature and pressure.

Chemical stability: Stable under normal temperature and pressure conditions.

Possibility of hazardous reactions: Liquefied Petroleum Gas (LPG): The combination of nickel, carbonyl, oxygen and N-butane with LPG results in explosion at temperatures between 20-40 ° C.
Sodium nitrite: Under the action of acids, or with incompatible materials.
Ethyl alcohol: Flammable product, can cause fire and explosions in contact with sources of heat and ignition.

Conditions to avoid: Elevated temperatures. Ignition sources. Contact with incompatible materials.

Incompatible material: Acids, Aliphatic amines, Alkali, Caustics, Chlorine, Isocyanates, Metals, Nickel, Nitric acid, Oxidizing Agents, Oxygen, Strong Acids, Strong base, Strong basic amines, Strong oxidizers, Strong Oxidizing agents and Sulphuric acid.

Hazardous decomposition products: There are no known hazardous decomposition products.

11 - TOXICOLOGICAL INFORMATION

Acute toxicity: Product not classified as acute toxic.
ATEmix Dermal: > 5000 mg/kg.
ATEmix Vapours (4h): > 20 mg/L.
ATEmix Oral: > 5000 mg/kg.
ATEmix Dusts and mists (4h): > 5 mg/L.

Skin corrosion/irritation: Causes mild skin irritation with redness and dryness.

Serious eye damage/irritation: Causes serious eye irritation with redness and pain.

Respiratory or skin sensitization: It is not expected to present respiratory or skin sensitization.

Germ cell mutagenicity: It is not expected to show mutagenicity in germ cells.

Carcinogenicity: It is not expected to be carcinogenic.

Reproductive toxicity: May damage fertility or the unborn child.

STOT - Single exposure: May cause drowsiness or dizziness, may cause dizziness and nausea.

STOT - Repeated exposure: Causes damage to the liver through prolonged or repeated exposure.

Aspiration hazard: It is not expected to present an aspiration hazard.

12 - ECOLOGICAL INFORMATION

Toxicity: Harmful to aquatic life with long lasting effects.

Information regarding to:

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 7/9

- Lauryl alcohol 7 EO:
NOEC (*Selenastrum capricornutum*, -): 0.31 mg/L;
LC₅₀ (*Cyprinus carpio*, 96 h): 1.4 mg/L;
EC₅₀ (*Daphnia magna*, 48 h): 6.46 mg/L.
- Myristic Oxide Amine:
ErC₅₀ (Green algae, 72 h): 0.19 mg/L;
LC₅₀ (Fish, 96 h): 2.67 mg/L;
EC₅₀ (*Daphnia magna*, 48 h): 3.1 mg/L.
- Sodium nitrite:
LC₅₀ (*Oncorhynchus mykiss*, 96 h): 0.56 - 1.78 mg/L;
EC₅₀ (*Daphnia magna*, 48 h): 12.5 - 100 mg/L.

Persistence and degradability: It is not expected to present persistence and degradability.

Bioaccumulative potential: Presents low bioaccumulative potential in aquatic organisms.
Information regarding to:
- Ethylic alcohol:
BCF: 3
- Lauryl alcohol 7 EO:
log K_{ow}: 3.4.

Mobility in soil: Not determined.

Other adverse effects: No other environmental effects known.

13 - DISPOSAL CONSIDERATIONS

Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific material.

Keep the material remains in its original and properly closed containers. Disposal should be performed as established for the material.

14 - TRANSPORT INFORMATION

Road: UN - United Nations: Model Regulations:
• Recommendations on the Transport of Dangerous Goods.

UN number: 1950

Proper shipping name: AEROSOLS

Primary risk class or division: 2.1

Subsidiary risk class or division: NA

Packing group: NA

Railway regulations: COTIF - Convention concerning International Carriage by Rail:
• Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.

UN number: 1950

Proper shipping name: AEROSOLS

Primary risk class or division: 2.1

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 8/9

division:

Subsidiary risk class or NA

division:

Packing group: NA

Sea: IMO - International Maritime Organization:

- IMDG Code - International Maritime Dangerous Goods Code.

UN number: 1950

Proper shipping name: AEROSOLS

Primary risk class or 2.1

division:

Subsidiary risk class or NA

division:

Packing group: NA

EmS: F-D,S-U

Environmental hazards: It's not considered a marine pollutant for transportation.

Air: IATA - International Air Transport Association:

- DGR - Dangerous Goods Regulation.

UN number: 1950

Proper shipping name: AEROSOLS

Primary risk class or 2.1

division:

Subsidiary risk class or NA

division:

Packing group: NA

Special precautions for user: Not applicable.

15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

16 - OTHER INFORMATION

This document was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Change control:

Version	Manufacture date	Changes
01	07/25/2023	Elaboration

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: Jimo Limpa Tecidos Aerossol

Revision: 01

Date: 10/26/2023

Pages: 9/9


Classification of the substance or mixture:
Health: 2
Flammability: 4
Instability: 0

Classification system adopted:
Hommel Diagram - National Fire Protection Association: NFPA 704

Classification of the substance or mixture:
Health: 3*
Flammability: 4
Physical Hazard: 0

Classification system adopted:
National Paint & Coatings Association: NPCA

NFPA 704:



HMIS:

HEALTH	*	3
FLAMMABILITY		4
PHYSICAL HAZARD		0
PERSONAL PROTECTION		

Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;
ATEmix - Acute Toxicity Estimate of the mixture;
BCF - Bioconcentration factor;
CAS - Chemical Abstracts Service;
EC₅₀ - Effective concentration of substance that causes 50 % of the maximum response;
ErC₅₀ - Effective concentration that results in a 50% reduction in the growth rate;
K_{ow} - Octanol-water partition coefficient;
LC₅₀ - Lethal Concentration 50%;
NIOSH - National Institute for Occupational Safety and Health;
NOEC - No Observed Effect Concentration;
OSHA - Occupational Safety & Health Administration;
PEL - Permissible Exposure Limit;
REL - Recommended Exposure Limit;
STEL - Short Term Exposure Limit;
TLV - Threshold Limit Value;
TWA - Time Weighted Average;
UN - United Nations.

Bibliographic references:

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs®). Cincinnati-USA, 2023.

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 9th rev. ed. New York: United Nations, 2021.