

## SAFETY DATA SHEET

**Product:** JIMO Desamassa

Revision: 04

Date: 09/09/2025

Pages: 1/8

### SECTION 1: IDENTIFICATION

GHS product identifier:	JIMO Desamassa
Other means of identification:	49911
Recommended use of the chemical and restrictions on use:	Remove wrinkles from clothes without ironing.
Supplier's details:	Jimo Química Industrial Ltda. <b>Address:</b> Rua Ítalo Raffo 693 - Distrito Industrial, CEP: 94930-240 - RS - Brasil. <b>Phone number:</b> +55 51 3470 67 55 <b>E-mail:</b> jimo@jimo.com.br
Emergency phone number:	+55 51 3470 67 55 / 0800 051 41 46

### SECTION 2: HAZARD IDENTIFICATION

Classification of the substance or mixture:	Aerosols - Category 2; Hazardous to the Aquatic Environment - Acute Hazard - Category 3; Hazardous to the Aquatic Environment - Chronic Hazard - Category 3.
Classification system adopted:	Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

#### GHS label elements, including precautionary statements

Pictograms:	
-------------	---

Signal word:	WARNING
Hazard statement(s):	H223 Flammable aerosol. H229 Pressurized container: may burst if heated. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement(s):	<b>PREVENTION:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.  <b>STORAGE:</b> P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  <b>DISPOSITION:</b> P501 Dispose of contents and container in accordance with local regulations.
Other hazards which do not result in classification:	The product has no other hazards.

## SAFETY DATA SHEET

**Product:** JIMO Desamassa

Revision: 04

Date: 09/09/2025

Pages: 2/8

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### MIXTURE

Components contributing to the hazard:

Product identifier	CAS/EC	Concentration range (%)
Liquefied Petroleum Gas (LPG)	68476-85-7	10 - 20
Propylene glycol ether	1569-01-3	1.50 - 2.10
Diquaternary polydimethylsiloxane <sup>1</sup>	NA	1.00 - 2.50
N-Ethyl-N-Soy Morpholine Ethosulfate	61791-34-2	0.1 - 1
Sodium nitrite	7632-00-0	0.1 - 1

<sup>1</sup> It does not have a CAS number because it is a mixture not registered in the Chemical Abstract Service database.

NA: Not applicable.

### SECTION 4: FIRST-AID MEASURES

#### Description of necessary first-aid measures

Inhalation:	Remove victim to fresh air.
Skin:	Wash exposed skin with sufficient amount of water to remove the product.
Eye:	Rinse carefully with water for several minutes. If wearing contact lenses, remove them if it is easy. If eye irritation occurs: consult a doctor. Bring this document.
Ingestion:	Wash the victim's mouth with plenty of water. Contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.
Most important symptoms/effects, acute and delayed:	No symptoms and effects are expected after exposure to the material.
Indication of immediate medical attention and special treatment needed, if necessary:	If necessary, provide symptomatic treatment.

### SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media:	Suitable: carbon dioxide (CO <sub>2</sub> ), water mist and dry chemical powder. Unsuitable: water directly onto the burning material.
Specific hazards arising from the chemical:	Combustion of the material or its packaging can form irritating and toxic gases such as carbon monoxide and dioxide. The combustion of the chemical product or its packaging can form irritating and toxic gases such as carbon monoxide and dioxide. Very dangerous when exposed to excessive heat or other sources of ignition such as: sparks, open flames or flames from matches and cigarettes, welding operations, pilot lamps and electric motors. Gases can be denser than air and can accumulate in low-lying or confined areas, such as storm drains and basements. They can travel long distances, causing flame regression or new fires in both open and confined environments. Containers may explode if heated.
Special protective actions for fire-fighters:	Do not extinguish a gas leak fire unless the leak can be contained. If cargo is involved in fire, isolate and evacuate the area within a minimum radius of 1600 meters. Use self-contained respiratory protection equipment (SCBA) with positive pressure and complete protective clothing. Containers

## SAFETY DATA SHEET

**Product:** JIMO Desamassa

Revision: 04

Date: 09/09/2025

Pages: 3/8

and tanks involved in the fire must be cooled with water mist.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:	Isolate the leakage from sources of ignition. Keep unauthorized persons out of the area and away from windows. Stop the leakage if it can be done without risk. Prevent sparks or flames. Do not smoke. Do not touch damaged containers or spilled product without proper clothing. Avoid exposure to the product. Stay in a safe place, with the wind at your back. Use personal protective equipment as described in section 8.
For emergency responders:	Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.
Environmental precautions:	Avoid that the spilled product reaches waterways or sewage system.
Methods and materials for containment and cleaning up:	Release contents slowly into the atmosphere. Stay downwind. Do not pour water into the spill or source of the leak. Due to the dispersion of the product in the environment, it is recommended that the area be ventilated until the area is released. All equipment used to contain the product must be grounded. Do not dispose of used or damaged containers directly into the environment or into the sewage system. Use non-sparking tools to collect absorbed product. For final disposal, proceed as per Section 13 of this document.

### SECTION 7: HANDLING AND STORAGE

#### Precautions for safe handling

Precautions for safe handling:	Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid gases and aerosols formation. Avoid exposure to the product, since the effects may not be felt immediately. Use personal protective equipment as described in section 8. Avoid contact with incompatible materials.
General hygiene:	Wash hands and face thoroughly after handling and before eating, drinking, smoking, or using the toilet. Contaminated clothing should be changed and washed before reuse. Remove contaminated clothing and protective equipment before entering eating areas.

#### Conditions for safe storage, including any incompatibilities

Technical measures for prevention of fire and explosion:	Keep away from heat, sparks, open flame, and hot surfaces. Do not smoke. Keep the container tightly closed. Ground the container vessel and product receiver during transfers. Only use non-sparking tools. Avoid the accumulation of electrostatic charges. Use explosion-proof electrical, ventilation, and lighting equipment.
Conditions for safe storage, including any incompatibilities:	Store in a dry, well-ventilated place away from sunlight. Keep the container closed. It is not necessary addition of stabilizers and antioxidants to ensure the durability. This material may react dangerously with some incompatible materials as outlined in Section 10. Keep away from incompatible materials.
Packaging compatibilities:	Similar to the original packaging.
Inadequate packaging materials:	There are not known unsuitable material.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

## SAFETY DATA SHEET

**Product:** JIMO Desamassa

Revision: 04

Date: 09/09/2025

Pages: 4/8

**Occupational exposure limit:** The values below apply to workplaces.

- Liquefied Petroleum Gas (LPG):  
OSHA - PEL - TWA: 1000 ppm (1800 mg/m<sup>3</sup>) (29 CFR 1910.1000 Table Z-1) (CFR);  
NIOSH - REL - TWA: 1000 ppm (1800 mg/m<sup>3</sup>);  
ACGIH - TLV - TWA: (AF; D; EX);
- Triethanolamine:  
ACGIH - TLV - TWA: 5 mg/m<sup>3</sup>.

D: Simple asphyxiant;  
EX: Explosion hazard: the substance is a flammable asphyxiant or excursions above the TLV® could approach 10% of the lower explosive limit;  
AF: See Appendix F: Minimal Oxygen Content.  
CFR: See mentioned item in OSHA CFR.

**Biological limit:** No biological indicators of exposure are established.

**Other limits and values:** No other limits and values are established.

**Appropriate engineering controls:** A risk assessment is recommended to define the engineering control measures necessary to eliminate or minimize the risk. These measures help to reduce exposure to the product. Maintain atmospheric concentrations of the constituents of the material below occupational exposure limits indicated.

### Individual protection measures, such as personal protective equipment (PPE)

**Eye/face protection:** Protective glasses.

**Skin protection:** Closed shoes and appropriate protective clothing. Suitable protective gloves.

**Respiratory protection:** A risk assessment should be performed for proper definition of respiratory protection, in view of the material use conditions.

**Thermal hazards:** It does not present thermal hazards.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Liquid, compressed.

**Colour:** Not applicable.

**Odour:** Not available.

**Melting point/freezing point:** Not applicable.

**Boiling point or initial boiling point and boiling range:** Not applicable.

**Flammability:** Not available.

**Lower and upper explosion limit/flammability limit:** Not applicable.

**Flash point:** Not applicable.

## SAFETY DATA SHEET

**Product:** JIMO Desamassa

Revision: 04

Date: 09/09/2025

Pages: 5/8

Auto-ignition temperature: Not available.

Decomposition temperature: Not applicable.

pH: 7 to 8.

Kinematic viscosity: Not applicable.

Solubility: Miscible in water.

Partition coefficient n-octanol/water (log value): Not available.

Vapour pressure: Not applicable.

Density and/or relative density: Not available.

Relative vapour density: Not applicable.

Particle characteristics: Not applicable.

Other information: Not applicable.

### SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reactivity is not to be expected under normal conditions of temperature and pressure.

Chemical stability: Stable under normal temperature and pressure conditions.

Possibility of hazardous reactions: - Liquefied Petroleum Gas (LPG):  
The combination of nickel, carbonyl, oxygen and N-butane with LPG results in explosion at temperatures between 20-40 ° C.

- Sodium nitrite:  
Under the action of acids, or with incompatible materials.

Conditions to avoid: High temperatures. Contact with incompatible materials.

Incompatible materials: Acids, alkali, chlorine, compounds with high affinity for hydroxyl groups, metals, nickel, oxidizing agents, oxygen, strong basic amines and strong oxidizing agents.

Hazardous decomposition products: No dangerous decomposition products are known.

### SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity: Product not classified as acute toxic.  
ATEmix Vapours (4h): > 20 mg/L.  
ATEmix Dusts and mists (4h): > 5 mg/L.  
ATEmix Oral: > 5000 mg/kg.  
ATEmix Dermal: > 5000 mg/kg.

Skin corrosion/irritation: It is not expected to cause skin irritation.

Serious eye damage/irritation: It is not expected to cause eye irritation.

## SAFETY DATA SHEET

**Product:** JIMO Desamassa

Revision: 04

Date: 09/09/2025

Pages: 6/8

Respiratory or skin sensitization:	It is not expected to present respiratory or skin sensitization.
Germ cell mutagenicity:	It is not expected to show mutagenicity in germ cells.
Carcinogenicity:	It is not expected to be carcinogenic.
Reproductive toxicity:	It is not expected to be reproductively toxic.
STOT - Single exposure:	It is not expected to exhibit specific target organ toxicity by single exposure.
STOT - Repeated exposure:	It is not expected to exhibit specific target organ toxicity on repeated exposure.
Aspiration hazard:	It is not expected to present an aspiration hazard.

### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:	Harmful to aquatic life with long lasting effects.  Information regarding to: - <u>Sodium nitrite</u> : LC <sub>50</sub> ( <i>Oncorhynchus mykiss</i> , 96 h): 0.56 - 1.78 mg/L; EC <sub>50</sub> ( <i>Daphnia magna</i> , 48 h): 12.5 - 100 mg/L.
Persistence and degradability:	It is not expected to present persistence and degradability.
Bioaccumulative potential:	Presents low bioaccumulative potencial in aquatic organisms. Information regarding to: - <u>Sodium benzoate</u> : log K <sub>ow</sub> : 2.27.
Mobility in soil:	Not determined.
Other adverse effects:	No other environmental effects known.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.  
Keep product residues in their original packaging and properly closed. Disposal must be carried out as established for the product.

### SECTION 14: TRANSPORT INFORMATION

<b>Road:</b>	UN - United Nations: Model Regulations: • Recommendations on the Transport of Dangerous Goods.
UN number:	1950
UN proper shipping name:	AEROSOLS
Transport hazard class(es):	2.1

## SAFETY DATA SHEET

**Product:** JIMO Desamassa

Revision: 04

Date: 09/09/2025

Pages: 7/8

Packing group: NA

Environmental hazards: The product is not considered dangerous for the environment for land transport.

**Railway regulations:** COTIF - Convention concerning International Carriage by Rail:  
• Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.

UN number: 1950

UN proper shipping name: AEROSOLS

Transport hazard class(es): 2.1

Packing group: NA

Environmental hazards: The product is not considered dangerous for the environment in rail transport.

**Sea:** IMO - International Maritime Organization:  
• IMDG Code - International Maritime Dangerous Goods Code.

UN number: 1950

UN proper shipping name: AEROSOLS

Transport hazard class(es): 2.1

Packing group: NA

Environmental hazards: It's not considered a marine pollutant for transportation.

EmS: F-D,S-U

**Air:** IATA - International Air Transport Association:  
• DGR - Dangerous Goods Regulation.

UN number: 1950

UN proper shipping name: AEROSOLS

Transport hazard class(es): 2.1

Packing group: NA

Environmental hazards: The product is not considered dangerous for the environment for air transport.

Special precautions for user: Not applicable.

Transport in bulk according to IMO instruments: Consult regulations:

- International Maritime Organization: MARPOL: Articles, protocols, annexes, unified interpretations of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto, consolidated edition. IMO, London, 2006;
- International Maritime Organization: IBC code: International code for the construction and equipment of shipping carrying dangerous chemicals in bulk: With Standards and guidelines relevant to the code. IMO, London, 2007.

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)- Chapter 1.5  
and Annex 4

## SAFETY DATA SHEET

**Product:** JIMO Desamassa

Revision: 04

Date: 09/09/2025

Pages: 8/8

### SECTION 15: REGULATORY INFORMATION

#### Safety, health and environmental regulations specific for the product in question

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

### SECTION 16: OTHER INFORMATION

This document was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other products, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

#### Change control:

Version	Manufacture date	Changes
04	09/09/2025	Change in section: 1.

#### Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;  
ATEmix - Acute Toxicity Estimate of the mixture;  
CAS - Chemical Abstracts Service;  
EC<sub>50</sub>- Effective concentration of substance that causes 50 % of the maximum response;  
IARC - International Agency for Research on Cancer;  
K<sub>ow</sub>- Octanol-water partition coefficient;  
LC<sub>50</sub>- Lethal Concentration 50%;  
NIOSH - National Institute for Occupational Safety and Health;  
OSHA - Occupational Safety & Health Administration;  
PBT - Persistent, bioaccumulative and toxic;  
PEL - Permissible Exposure Limit;  
REL - Recommended Exposure Limit;  
TLV - Threshold Limit Value;  
TWA - Time Weighted Average;  
UN - United Nations;  
vPvB - Very Persistent and very Bioaccumulative.

#### Bibliographic references:

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs®). Cincinnati-USA, 2025.

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 10th rev. ed. New York and Geneva: United Nations, 2023.